

# UVivid

UV Narrow Web Printing Inks

## UVivid RVA394

UV Roller Coater Gloss Coating

### Features

- UV based
- High gloss finish
- Low odour
- Good gloss retention
- Good scratch resistance
- Ready to use
- Excellent flow & transfer for smoother application

# Speciality Varnishes

UV Roller Coater Gloss Coating

### SUBSTRATE

Coated Paper and Board (On synthetic substrate suitability / adhesion should always be confirmed prior to use). Care should be taken while coating low GSM Paper to avoid curling.

### Product Packing:

Available in 20 Kg pack size.

TEST RVA394 FOR SUITABILITY  
BEFORE PRODUCTION RUN.

**SERICOL**  
More than ink...Solutions.  
FUJIFILM

## UVivid RVA394

<b>Application:</b>	Online / Offline Roller Coater product.
<b>Typical viscosity range:</b>	45 ± 5 sec @30°C by Ford Cup No. B – 4.
<b>Recommended Coating Weight:</b>	3-5 GSM (as per needed).
<b>Printing Speed / Curing Speed / Gloss:</b>	<p>Following factors can influence the printing speed, curing and gloss of RVA394</p> <ul style="list-style-type: none"><li>* Coating weight.</li><li>* Substrate (absorbent/non -absorbent).</li><li>* Type, Voltage, Age of UV lamps.</li><li>* Printing –screen and solids</li><li>* Machine speed.</li><li>* Light and Dark colors.</li></ul>
<b>UV Lamps:</b>	Power OF UV lamps should be - 120 W/cm (300 W/in.).
<b>Storage &amp; Shelf life:</b>	UV curable varnish should be stored and handled in amber glass, baked phenolic lined, stainless steel, or polyethylene lined containers. A head space should be present in any storage container to support the oxygen requirements of the inhibitor. This material should be stored in the dark and at temperatures not exceeding 90°F/32°C. Exposure to direct sun light, freezing & heat should be avoided. Shelf life - 6 months from date of manufacture..
<b>Safety &amp; Handling:</b>	Materials in this varnish can cause eye and skin irritation and have potential to cause skin sensitization in susceptible individuals. Proper industrial hygiene practices should be utilized. Please read Material Safety Data Sheet before using.

## UVivid RVA394

*The above information is based on our experience as well as on internal standardized tests and is not to be interpreted as a warranty or guarantee in any form, as conditions beyond our control can affect the quality of printing. In case of doubt, the user should always make every effort to ensure that the products used are appropriate for the purpose.*

**SERICOL**  
More than ink...Solutions.  
**FUJIFILM**

### FUJIFILM SERICOL INDIA PVT LTD,

10/11,B.U.Bhandari Industrial estate. Sanaswadi, Tal. Shirur, Dist. Pune, Maharashtra, India 412 208,  
Tel.: 02137 392500/537, Fax: 02137 392555  
E-mail: [fsid.customercare@fujifilm.com](mailto:fsid.customercare@fujifilm.com)  
Customer Care Tel: +91(0) 2137 392552  
Technical Help line: +91 (0) 2137 392523/524/525,  
Website: [www.fujifilmsericol.in](http://www.fujifilmsericol.in)

#### Mumbai

Industrial Gala No. 20, Building 'A',  
Ground Floor Gami Industrial Park,  
Plot No. C-39A, TTC Industrial Area  
Pawane, Turbhe Kalyan Road, MIDC,  
Navi Mumbai, Pin : 400705  
E-mail: [vaibhav.dhande@fujifilm.com](mailto:vaibhav.dhande@fujifilm.com)

#### Chennai

New No.7; Old No 147, Mount Road, Saidapet  
Tel : +91 (0) 44 22353239  
Fax : +91 (0) 44 22301383  
E-mail: [FSID.chennai@fujifilm.com](mailto:FSID.chennai@fujifilm.com)

#### Tirupur

18/2, K.V.R. Nagar, Main Road, Near Nair Hospital,  
Karuvampalayam, Tirupur 641 604  
Tel: (0421) 2232850/22326972  
E-mail: [FSID.tirupur@fujifilm.com](mailto:FSID.tirupur@fujifilm.com)

#### Delhi

B50, Naraina Ind Area, Phase II, Near Batra Banquet Hall,  
New Delhi-110028.  
Tel.: +91-11-25893346 / 47 Fax: +91-11-25893346  
E-mail: [FSID.delhi@fujifilm.com](mailto:FSID.delhi@fujifilm.com)

#### Kolkata

16/1 Panchnantala Road, Belgharia, Kolkata -700056.  
West Bengal Tel.: +91-033 - 25560450  
Fax: +91-033 - 25560450  
E-mail: [dipankar.sasmal@fujifilm.com](mailto:dipankar.sasmal@fujifilm.com)

#### Srilanka

99, Stace Road, Colombo 14, Sri Lanka.  
Tel : + 94 (0) 11 2436529  
Fax : + 94 (0) 11 2 449907  
Mobile : + 94 777 899 273